

The Hyper Photonix HSO6-800-DR-P8S transceiver is designed for 800G Ethernet and InfiniBand communication application links over 500m of single-mode fiber(SMF), and it is compliant with OSFP MSA, 800G Pluggable MSA, CMIS 5.1, IEEE802.3ck and IEEE 802.3df standards. The optical signal is transmitted over eight parallel channels at a central wavelength of 1310nm. The module contains 8 parallel channels on the transmitter and receiver, each operating at 106.25Gbps. It is suitable for 800G Ethernet, Data Center, InfiniBand, Breakout 2x400G DR4 or 8x100G DR Application. The optical interface is 2*MPO-12/APC connector.

Features

- OSFP MSA 5.0 and CMIS 5.1 compliant
- Two MPO-12/APC optical connectors
- 8x106.25Gbps (53.125GBd PAM4) electrical interface
- 8x106.25Gbps (53.125GBd PAM4) optical interface
- Up to 500m over SMF
- Power dissipation ≤ 18W
- Operating case temperature: 0°C to 70°C
- IEEE802.3ck and IEEE 802.3df compliant
- Built-in digital diagnostic functions
- 3.3V power supply voltage
- RoHS compliant



Applications

- 800G Ethernet
- Datacenter networks
- InfiniBand NDR

Specifications

Part Number	HSO6-800-DR-P8S
Data Rate	800Gbps
Supply Voltage	3.3V
Power Consumption	≤ 18W
Wavelength	1310nm
Optical Connector	Dual MPO-12/APC
Transmitter	Hyper Silicon™ Photonics
Case Temperature	0°C to 70°C
Reach	500m over SMF